



All the patents are held accountable counterfeiting.

Features



Green Power

DIMENSIONS: 210(L)*110(W)*109.5(H)mm
WEIGHTS: 1790g

- Comply with High Efficiency Power 80Plus Criterion
- Din Rail/ Screw Mounting Dual Purpose
- Fan speed control(PCB damp proof process)
- Protection with constant current
- Output Voltage Digital Display
- 100% full load burn-in test
- MOSFET designed
- 110,000Hrs MTBF per MIL-HDBK-217F
- 1-year warranty
- Output modify range: 3V~200VDC
- Split rail & Series connection possible

General specifications

INPUT

Input range	180~264VAC 220~380VDC
Input frequency	47~63Hz
Inrush current (25° C)	40A/220VAC

OUTPUT


Hold-up time	10mS
Short protection	Autorecovery
Overload protection	Constant current protection
Over voltage protection	Autorecovery
Power Ready Signal (Optional)	
Redundant function (Optional)	

Detail specifications

1000 Watts

MODEL	O/P Volt Adj. ± %	Load(Current) ¹			Ripple & Noise ⁴	Line REG. ²	Load REG. ³	Efficiency ⁵	O.V.P. Trip point
		Min.	Rated	Max.					
LP11K0D-12T	V1: +12V ±10%	0A	83.3A	83.3A	150mVp-p	±1%	±3%	82% Min.	14 ~ 17V
LP11K0D-24T	V1: +24V ±10%	0A	41.6A	41.6A	300mVp-p	±1%	±3%	83% Min.	27.6 ~ 31V
LP11K0D-48T	V1: +48V ±10%	0A	20.83A	20.83A	480mVp-p	±1%	±3%	83% Min.	55 ~ 67V
LP11K0D-110T	V1: +110V ±10%	0A	9.1A	9.1A	1500mVp-p	1%	3%	86% Min.	

Rdy Connection



Please Choose Fit Function, And Fill In The Blank With Suitable Words.

Order Model: LP11K0D-24 T

Optional Function:

Terminal Block: "T" : PCB Barrier Terminal Block

Without Function: "N"

Power Ready Signal and Redundant

EMC Standards

EN55 022 CLAS S A, EN50 082-1
ENV5 0204, EN61 000-3-3
EN61 00-4-2, EN61 00-4-3,
EN61 000-4-4, EN61 000-4-5,
EN61 000-4-6, EN61 000-4-11

Safety Standards

CE CE Marking

Environments

Operating Temperature	-15 ~ 50°C, Ambient
Operating Humidity	5 ~ 95% RH, No Condensing
Storage Temperature	-20 ~ 85°C, Ambient
Vibration	2G, 10~500Hz, 3 axes

- NOTE:**
1. Each output can provide up to maximum load, but total load can not exceed rated output power.
 2. Line regulation is measured from low line to high line at rated load.
 3. Load regulation is measured from 20% to 100% of rated load at 220VAC input. (Redundant function Sepc. 0.6V Add.)
 4. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1uf & 47uf parallel capacitor.
 5. Efficiency is measured at rated load and 220VAC input.
 6. Hold-up time is measured at rated load and 220VAC input.
 7. Reign Power reserve the right to change specifications at any time without notice.