



Features

General specifications



DIMENSIONS: 52.5(L)x22.5(W)x27.5(H)mm
WEIGHTS: 23.7g

- Convection cooled
- Internal short, overload Protection
- 100% burn-in test
- **Constant Current designed, Low Price**
- **Output Constant current modify range:50~100%**
- **PFC high efficiency designed**
- **2 years Warranty**

INPUT

Input range 100~240VAC
 Input frequency 47~63Hz
 Inrush current (25° C) 30A/ 110VAC
 65A/ 220VAC
 Power factor 90% Min.

OUTPUT

Short protection Autorecovery

Detail specifications

5 Watts (constant current)

MODEL	O/P Volt	Load(Current) ¹	Current Load ²	Efficiency ³
		Rated		
LA1005-12C	V: +11V~17V	330mA±5%	11V~14V±10% 14V~17V±5%	85% ref.

Environments

Operating Temperature -15 ~ 50°C, Ambient
 Operating Humidity 5 ~ 95% RH, No Condensing
 Storage Temperature -40 ~ 85°C, Ambient

- NOTE:**
1. Each output can provide up to maximum load, but total load can not exceed rated output power.
 2. The load adjustment is measure 100 ~ 240VAC input . In accord with Constant Voltage (CV model) to test.
 3. Efficiency is measured at rated load and 220VAC/60Hz/25°C input.
 4. Reign Power reserve the right to change specifications at any time without notice.